```
readSourceFile sourceFile

server = http.createServer (request, response) ->
  response.end "#{countWords(fileContents)}"

server.listen 8080, '127.0.0.1'
```

Exercises 3.4.4

```
accumulate = (initial, items, accumulator) ->
  total = initial
  for item in items
    total = accumulator total, item
  total

sumFractions = (fractions) ->
  accumulator = (lhs, rhs) ->
    if lhs is '0/0'
      rhs
    else if rhs is '0/0'
      lhs
    else
      lhsSplit = lhs.split /\//gi
      rhsSplit = rhs.split /\//gi
      lhsNumer = 1*lhsSplit[0]
      lhsDenom = 1*lhsSplit[1]
      rhsNumer = 1*rhsSplit[0]
      rhsDenom = 1*rhsSplit[1]
      if lhsDenom isnt rhsDenom
        commonDenom = lhsDenom*rhsDenom
      else
        commonDenom = lhsDenom

      sumNumer = lhsNumer*(commonDenom/lhsDenom) + rhsNumer*
(commonDenom/rhsDenom)
      "#{sumNumer}/#{commonDenom}"

  accumulate '0/0', fractions, accumulator

console.log sumFractions ['2/6', '1/4']
# '14/24'
```

And the keep function:

```
keep = (arr, cond) ->
  item for item in arr when cond item
```