```
houseRoast = 'Yirgacheffe'

hasMilk = (style) ->
  switch style.toLowerCase()
    when 'latte', 'cappuccino', 'mocha'
      yes
    else
      no

makeCoffee = (requestedStyle) ->
  style = requestedStyle || 'Espresso'
  console.log houseRoast
  if houseRoast?
    "#{houseRoast} #{style}"
  else

    style

barista = (style) ->
  time = (new Date()).getHours()
  if hasMilk(style) and time > 12 then "No!"
  else
    coffee = makeCoffee style
    "Enjoy your #{coffee}!"

order = document.querySelector '#order'
request = document.querySelector '#request'
response = document.querySelector '#response'

order.onsubmit = ->
  response.innerHTML = barista(request.value)
  false
```

When the order element (a form) is submitted, then evaluate the following function.

Find the parts of the HTML document that you need to interact with. Assign references to them to variables.

Use innerHTML to set the content of the response element to be the order response.

Return false from the function so that the order form doesn't submit.

This program accepts the coffee order from an input field and displays the response in the web page.

2.8.2. Running on the command line

If you run CoffeeScript from a standard install on the command line and provide a CoffeeScript file (such as the one from listing 2.4), then the program in the file will be executed:

```
> coffee 2.4.coffee
You need to specify an order.
```