```
fs = require 'fs'

houseRoast = null

hasMilk = (style) ->
  switch style.toLowerCase()
    when "latte", "cappuccino"
      yes
    else
      no

makeCoffee = (requestedStyle) ->
  style = requestedStyle || 'Espresso'
  if houseRoast?
    "#{houseRoast} #{style}"
  else
    style

barista = (style) ->
  time = (new Date()).getHours()
  if hasMilk(style) and time > 12 then "No!"
  else


    coffee = makeCoffee style
    "Enjoy your #{coffee}!"
main = ->
  requestedCoffee = process.argv[2]
  if !requestedCoffee?
    console.log 'You need to specify an order'
  else
    fs.readFile 'house_roast.txt', 'utf-8', (err, data) ->
      if data then houseRoast = data.replace /\n/, ''
      console.log barista(requestedCoffee)

main()
```

Read the command-line input.

Read the file containing the house roast and set it.

Call the barista program with the command-line argument.

The program in listing 2.4 expects to find a file called house_roast.txt that contains the name of the house roast. Suppose that file contains Yirgacheffe and that it's currently before midday. Here's some sample output:

```
> coffee 2.4.coffee
You need to specify an order.

> coffee 2.4.coffee 'Ristretto'
Enjoy your Yirgacheffe Ristretto!
```

The output you'll get when you invoke the program depends on the order and the time of day; experiment with it and explore how it works. The programs in listings 2.3 and 2.4 use some concepts in CoffeeScript and related to CoffeeScript (such as asynchronous programs and web browsers)