```
OPTIONS /api/posts HTTP/1.1
Origin: http://localhost:1111
Access-Control-Request-Method: DELETE
Access-Control-Request-Headers: Shady-Status
```

Table 4.5 Various ways to reject a CORS preflight request

Response	Reason
`HTTP/1.1 200 OK`	No Access-Control-Allow-Origin header
`HTTP/1.1 200 OK` `Access-Control-Allow-Origin: *`	No Access-Control-Allow-Methods header

`HTTP/1.1 200 OK`
`Access-Control-Allow-Origin: *`
`Access-Control-Allow-Methods: DELETE`
	No Access-Control-Allow-Headers header

`HTTP/1.1 200 OK`
`Access-Control-Allow-Origin: *`
`Access-Control-Allow-Methods: DELETE`
`Access-Control-Allow-Headers: Foo`
	Access-Control-Allow-Headers doesn't match

`HTTP/1.1 200 OK`
`Access-Control-Allow-Origin: *`
`Access-Control-Allow-Methods: GET`
`Access-Control-Allow-Headers: Shady-Status`
	Access-Control-Allow-Methods doesn't match

As you can see, there are a lot of ways to reject a preflight request. Which one should you choose? Chapter 6 provides guidance for rejecting CORS requests.

The last few sections threw a lot of information your way. The next section takes a step back and reviews what you've learned so far.

4.5 Recapping preflights

The first thing you may have noticed is that there are a lot of different headers involved when working with preflights. Table 4.6 recaps these headers and what they mean.

Table 4.6 Preflight request headers and their corresponding response headers

Request header	Details	Response header	Details
Access-Control-Request-Method	Indicates the HTTP method for the actual request	Access-Control-Allow-Methods	Indicates which HTTP methods are supported at that endpoint Can contain multiple values
Access-Control-Request-Headers	Indicates additional headers on the request Can contain multiple values Optional	Access-Control-Allow-Headers	Indicates which HTTP headers are supported at that endpoint Can contain multiple values