
A simple way to distinguish these headers is to remember that any header starting with "Access-Control-Request-" is a request header added by the browser asking the server for permissions, and any header starting with "Access-Control-Allow-" is a response header sent by the server that grants permissions.

Figure 4.18 revisits the end-to-end flow from figure 4.2, except this time it includes the header and code that is exchanged among the client, browser, and server. The




```
var xhr = createXhr('GET',
                    'http://127.0.0.1:9999/api/posts');
xhr.setRequestHeader('Timezone-Offset',
                     new Date().getTimezoneOffset());
xhr.setRequestHeader('Sample-Source',
                     'CORS in Action');
xhr.send();
```

1 Client initiates request to server through browser

```
OPTIONS /api/posts HTTP/1.1
User-Agent: Chrome
Host: 127.0.0.1:9999
Accept: */*
Origin: http://localhost:1111
Access-Control-Request-Method: GET
Access-Control-Request-Headers:
Timezone-Offset, X-Sample-Source
```

2 Browser sends preflight request

```
HTTP 204
Access-Control-Allow-Origin: http:
//localhost:1111
Access-Control-Allow-Methods: GET
Access-Control-Allow-Headers:
Timezone-Offset, X-Sample-Source
```

3 Server sends preflight response

```
GET /api/posts HTTP/1.1
User-Agent: Chrome
Host: 127.0.0.1:9999
Accept: */*
Origin: http://localhost:1111
Timezone-Offset: 300
Sample-Source: CORS in Action
```

4 Browser sends actual request

```
HTTP 200
Access-Control-Allow-Origin:
http://localhost:1111

{
  "1": {"post", "..."},
  "2": {"post", "..."},
  "3": {"post", "..."}
}
```

5 Server sends actual response

6 Client receives actual response

```
xhr.onload = function() {
  var data = JSON.parse(xhr.responseText);
  // Process the response here.
};
```

Figure 4.18 End-to-end CORS request flow (with preflight)