Looking at the actual request, there is no information that connects it to the original preflight request. This can be confusing because we think of the preflight plus the actual request as occurring in tandem. If your server receives the actual request, you have to trust that the browser did the right thing and sent the preflight request before it. This highlights how crucial the browser is when making a CORS request.

Because the preflight request is stateless, it's important that all CORS responses include the Access-Control-Allow-Origin header. It's not enough to include the Access-Control-Allow-Origin header on just the preflight response. Both the preflight response and the actual response need the Access-Control-Allow-Origin header, as shown in table 4.8.

**Table 4.8 Both the preflight response and the actual response need the Access-Control-Allow-Origin header.**

| Response type | HTTP response |
|---|---|
| Preflight | `HTTP/1.1 204 No Content`<br>**`Access-Control-Allow-Origin: *`**<br>`Access-Control-Allow-Methods: GET, DELETE`<br>`Access-Control-Allow-Headers: Timezone-Offset, Sample-Source` |
| Actual | `HTTP/1.1 200 OK`<br>**`Access-Control-Allow-Origin: *`**<br>`Content-Type: application/json` |

If neither the preflight response nor the actual response has an Access-Control-Allow-Origin header, the CORS request will be rejected.

#### PREFLIGHT REQUESTS AND UPLOAD EVENTS

The discussion in this chapter has been focused on making HTTP requests, but a preflight request can also be issued on upload events. Upload events provide progress information about an upload. The following code shows how to use upload events to show a status message for an upload:

```
function uploadFile(file) {
  var xhr = new XMLHttpRequest();
  xhr.open('POST', '/upload', true);

  xhr.upload.onprogress = function(e) {
    console.log('Upload progress: ' ((e.loaded / e.total) * 100));
  };

  xhr.send(file);
}
```

The request needs to have a preflight because upload events are a new concept. Before upload support in `XMLHttpRequests` existed, the traditional way of doing an upload was through a form. While the form would upload a file, it couldn't provide additional information, such as how far the upload has progressed. The upload event