SERVER-SIDE COOKIE SUPPORT

The server indicates that it can receive cookies on CORS requests by setting the Access-Control-Allow-Credentials response header. Setting that header to `true` means that the server allows cookies on the CORS request.

If the request includes a preflight request, the Access-Control-Allow-Credentials header must be present on both the preflight and the actual request. But the cookie will only be sent on the actual request; the preflight request will never have a cookie.

The following listing modifies the server code to enable cookie support by adding the Access-Control-Allow-Credentials header.

Listing 5.3 Adding the Access-Control-Allow-Credentials header

```
var handleCors = function(req, res, next) {
  res.set('Access-Control-Allow-Origin', 'http://localhost:1111');
  res.set('Access-Control-Allow-Credentials', 'true');
  if (isPreflight(req)) {
    res.set('Access-Control-Allow-Methods', 'GET, DELETE');
    res.set('Access-Control-Allow-Headers',
            'Timezone-Offset, Sample-Source');
    res.set('Access-Control-Max-Age', '120');
    res.status(204).end();
    return;
  }
  next();
};
```

Sets Access-Control-Allow-Credentials header on both the preflight and actual request

But even with this server-side support, the delete request still fails. This is because the client needs to be configured to send cookies with the request. Let's update the client to do that.

CLIENT-SIDE COOKIE SUPPORT

In addition to setting a server-side response header, you have to set a property in the client's JavaScript code to include the cookie with the request. Chapter 2 introduced the `withCredentials` property, which controls cookie behavior. The default value for this property is `false`, which indicates that cookies aren't included on requests. Setting the `withCredentials` property to `true` includes cookies on cross-origin requests (this property has no effect on same-origin requests, which always include cookies). The following listing updates the client code to set the `withCredentials` property to `true`.

Listing 5.4 Setting `withCredentials` to `true` in the client code

```
var deletePost = function(postId) {
  var url = 'http://127.0.0.1:9999/api/posts/' + postId;
  var xhr = createXhr('DELETE', url);
  xhr.withCredentials = true;
  xhr.onload = function() {
    if (xhr.status == 204) {
      var element = document.getElementById('postId' + postId);
      element.parentNode.removeChild(element);
    }
```

Indicates that cookies are included with the request