aren't set. All the examples from chapters 3 and 4 behave this way. Because those examples didn't set any cookies, `withCredentials` and Access-Control-Allow-Credentials weren't necessary.

Table 5.3 Client code and server HTTP response when `withCredentials` and Access-Control-Allow-Credentials are both `true`

Client code	Server HTTP response

`var xhr = new XMLHttpRequest();`
`xhr.open('GET',`
`'http://127.0.0.1:9999/api/posts');`
`xhr.withCredentials = true;`
`xhr.send();`
	`HTTP/1.1 200 OK`
	`Access-Control-Allow-Origin:`
	`http://localhost:1111`
	`Access-Control-Allow-Credentials:`
	`true`

This section already covered what happens when both `withCredentials` and Access-Control-Allow-Credentials are `true`. There is really not much more to say here: if a cookie exists, it will be included with the CORS request. But things get a little more interesting for the next two cases, where one property is set and the other isn't.

Table 5.4 Client code and server HTTP response when `withCredentials` isn't set but Access-Control-Allow-Credentials is `true`

Client code	Server HTTP response

`var xhr = new XMLHttpRequest();`
`xhr.open('GET',`
`'http://127.0.0.1:9999/api/`
`posts');`
`xhr.send();`
	`HTTP/1.1 200 OK`
	`Access-Control-Allow-Origin:`
	`http://localhost:1111`
	`Access-Control-Allow-Credentials:`
	`true`

In this case, the server sets the Access-Control-Allow-Credentials header to `true`, even though the client doesn't set the `withCredentials` property. Although the values of the two don't match, the request still succeeds.

Here is how this combination works. When the server responds with an `Access-Control-Allow-Credentials: true` header, it's saying that it's okay to send cookies with the request. But because the `withCredentials` property isn't set, the CORS request doesn't include the cookie. From the server's perspective, the request looks like a normal CORS request without any cookies. The Access-Control-Allow-Credentials header isn't saying that cookies must be included in the request. It's merely suggesting that cookies can be included in the request. The client, armed with the `withCredentials` property, has the final say in whether or not cookies are included.

Setting `withCredentials` to `true` without an Access-Control-Allow-Credentials header is the only combination that returns an error (table 5.5). Because `withCredentials` is set to `true`, the cookies will be included with the request. But because Access-Control-Allow-Credentials isn't set, the server declares that cookies aren't allowed on the request. There is a conflict in expectations, and the request is rejected.