```
  allowMethods: ['GET', 'DELETE'],
  allowHeaders: ['Timezone-Offset', 'Sample-Source'],
  maxAge: 120,
  exposeHeaders: ['X-Powered-By']
};

var handleCors = function(options) {
  return function(req, res, next) {
    ...
    if (isPreflight(req)) {
      ...
      res.status(204).end();
      return;
    } else if (options.exposeHeaders) {
      res.set('Access-Control-Expose-Headers',
          options.exposeHeaders.join(','));
    }
```

New exposeHeaders option specifies which headers to expose

Sets Access-Control-Expose-Headers on nonpreflight responses

The `exposeHeaders` option specifies the response headers that should be exposed to the client. If the `exposeHeaders` property exists and the request isn't a preflight request, the Access-Control-Expose-Headers header is set to the values in the `exposeHeaders` array.

Table 6.7 summarizes common response headers that may be useful to clients. If your server sets one of the headers listed in the table, it may be useful to expose these to clients.

Table 6.7 Common response headers

Response header	Description
Content-Length	The number of bytes in the response body.
Date	The date the server sent the response.
ETag	A unique identifier that identifies a particular version of a resource. Used in conjunction with the If-Match and If-None-Match request headers to determine whether a resource has changed.
Expires	The date after which the resource is considered stale. Can be used in conjunction with the ETag or Date header to retrieve fresh content from the server.
Last-Modified	The date the resource was last modified.

It would be convenient to support a `*` value for the `exposeHeaders` option (similar to how you did for the `allowHeaders` option). A `*` value would mean that all response headers should be exposed to the client. To do this, the code needs to keep track of all the headers in the response. Unfortunately, NodeJS and Express don't provide convenient mechanisms for reading the response headers before the response is sent to the client. Other platforms, such as Java servlets, provide a mechanism for doing this. If you're using a language that supports this feature, you can use it to configure the Access-Control-Expose-Headers header.