- Access-Control-Allow-Methods:
  - This header only needs to be present on preflight responses.
  - It indicates which HTTP methods are allowed on a URL.
  - Common values include `HEAD`, `OPTIONS`, `GET`, `POST`, `PUT`, `PATCH`, and `DELETE`.
- Access-Control-Allow-Headers:
  - This header only needs to be present on preflight responses.
  - It indicates which HTTP headers are allowed on a URL.
  - Echo the Access-Control-Request-Headers value to get full header support.
- Access-Control-Max-Age:
  - This header only needs to be present on preflight responses.
  - It indicates how many seconds to cache preflight requests for.
  - Browsers may have their own `maxAge` caps.
- Access-Control-Expose-Headers:
  - This header indicates which response headers to expose to clients.
  - It's an optional header that isn't required for a successful CORS request.

The chapter also took a look at the security of CORS. It's important to remember that CORS in and of itself doesn't also serve as a mechanism for securing a server. If you need to serve protected content, consider some other authorization mechanism, such as cookies or OAuth2. If your CORS implementation allows cookies, it's also important to have CSRF protection in place.

Finally, this chapter examined how to minimize preflight requests by reducing the circumstances that lead to preflights. Reducing preflight requests is desirable because it eliminates an extra HTTP request, which can be expensive on resource-constrained devices such as mobile phones.