


**Figure 7.3 Error message from the missing request header**

### 7.2.1 Using the console

The console can be found in the developer tools and under the Console tab (if it isn't already selected). The console serves two purposes:

- It logs any messages or errors that occur while a site loads and runs.
- It allows you to enter JavaScript commands that can be run against the page.

The console is the first place to check when something on the page goes wrong. With that in mind, if you reload the sample client, the error from figure 7.3 should appear.

The text of the error message may differ from browser to browser. Chrome and Safari happen to give very detailed error messages for CORS errors. In the message from figure 7.3, you can see exactly what is wrong: "Request header field Sample-Source isn't allowed by Access-Control-Allow-Headers."

The console also lets you run JavaScript commands from the page. If you made changes to the server, you could reissue the CORS request without reloading the page by calling the `getBlogPosts` function directly. To do this, type `getBlogPosts()` in the console window and press Enter. Because the request will still fail, you'll see the same error message as in figure 7.3.

So, the console tells you what the error is, but not much more. To debug this request further, you need to look at the HTTP request itself. This can be done from the Network tab.

### 7.2.2 Using the Network tab

The Network tab shows the HTTP requests and responses from a page, as shown in figure 7.4. This includes requests for CSS style sheets, JavaScript files, images, fonts, WebSockets, and any HTTP requests triggered from `XMLHttpRequests`.

The Network tab for the sample shows two requests:

- The client.html page itself
- The CORS request to load the blog posts

The request to load the blog posts, shown in the bottom row, is a failing request.

The Network tab also provides additional information about the request, also shown in figure 7.4. This includes information such as the HTTP method, the HTTP status, the content type of the request, the location on the page that initiated the request, the size of the response, and the time it takes to load the response.