cross-origin requests. The next section looks at how to use a network sniffer like Wireshark to view the HTTP request and response headers.

7.3 Monitoring network traffic

Sometimes Chrome developer tools won't show all the HTTP header information. To see this in action, let's once again break the sample code, but in a different way. The following code snippet removes the Timezone-Offset and Sample-Source custom request headers from the client.html file:

```
var xhr = createXhr('GET', 'http://127.0.0.1:9999/api/posts');
xhr.onload = function() {
  var data = JSON.parse(xhr.responseText);
...
```

Removes Timezone-Offset and Sample-Source request headers from client.html

Next, the app.js server code is updated to remove the client http://localhost:1111 from the whitelist:

```
var originWhitelist = [
  'null'
];
```

Removes http://localhost:1111 from whitelist in app.js

This essentially means that the client won't be able to make requests, because there won't be an Access-Control-Allow-Origin header in the response. If you restart the sample and reload the page, you'll once again see an error, but there will be some slight differences.

Figure 7.6 shows the Console and Network tabs for the request to /api/posts. The request still fails, but this time the failure is on the actual `GET` request, because there is no preflight request. (Remember there is no preflight request because you removed the custom request headers from the request.) The HTTP status is labeled as `(canceled)`. Clicking the request itself shows that while you can see the request headers, the response headers are missing and there is an error that says "CAUTION: Provisional headers are shown." This error means that the response headers are unavailable. In this particular case, because the CORS request fails, the browser follows the conservative route and hides any response information, even though an HTTP response was sent to the server.

Even though Chrome won't display the response headers, there are other options available. You could always try a different browser. Browsers such as Internet Explorer and Firefox will display the response headers (although it's possible that they could change this behavior in the future).

Another option is to use a packet analyzer, such as Wireshark or Fiddler. Packet analyzers show all the network traffic flowing through your system, including the cross-origin request from the browser. The rest of this section explores how to use Wireshark or Fiddler to capture and view network traffic.