Table A.1 Request headers on all CORS requests

Header	Included on preflight request, actual request, or both?	Details
Origin	Both	The client's origin. For example, for a request from http://www.example.com/sample/path, the Origin header value would be http://www.example.com. Required on all CORS requests (preflight and actual). Some browsers may add the Origin header on same-origin `PUT`, `POST`, and `DELETE` requests. The origin is defined in RFC6454 "The Web Origin Concept" (http://tools.ietf.org/html/rfc6454). This spec is separate from the CORS spec.
Access-Control-Request-Headers	Preflight	A comma-separated list of headers the client would like to send on the actual request. Used during a preflight request to ask the server's permission to send certain request headers. Simple headers (defined in A.2.2) may not be included in this header.
Access-Control-Request-Method	Preflight	The HTTP method the client would like to use for the actual request. This header is required on all preflight requests, even if the value is a simple method (defined in A.2.1).

Table A.1 Response headers on all CORS responses

Header	Included on preflight response, actual response, or both?	Details
Access-Control-Allow-Credentials	Both	The header has only one valid value: `true`. This header is optional. Its presence with `true` value indicates that the server allows user credentials such as cookies on cross-origin requests. If the client would like to include user credentials on cross-origin requests, they must also set the `XMLHttpRequest`'s `withCredentials` property to `true`. If the server doesn't allow user credentials on cross-origin requests, this header should be omitted.
Access-Control-Allow-Headers	Preflight	A comma-separated list of headers that the server allows on cross-origin requests. If a value is a simple header (defined in A.2.2), it doesn't need to be included in this header. Adding headers in the list causes no harm.
Access-Control-Allow-Methods	Preflight	A comma-separated list of HTTP methods that the server allows on cross-origin requests. If the value is a simple method (defined in A.2.1), it doesn't need to be included in this header.