Table A.1 Response headers on all CORS responses *(continued)*

Header	Included on preflight response, actual response, or both?	Details
Access-Control-Allow-Origin	Both	Gives permission to make a cross-origin request. Valid values include: `*`, `null`, or the client's actual origin value (for example, http://www.example.com). Required on all CORS responses.
Access-Control-Expose-Headers	Actual	A comma-separated list of HTTP headers. Indicates which response headers a client can read from the server's response. If a header is a simple response header (defined in A.2.3), it doesn't need to be included in this list.
Access-Control-Max-Age	Preflight	The number of seconds the preflight request cache should store the preflight response. Browsers may cap this value. Chrome won't cache preflight responses for more than 5 minutes, while Firefox won't cache preflight responses for more than 24 hours.

A.2 Other terms used in CORS

In addition to the headers just noted, there are a few other important terms used by CORS.

Simple method

A *simple method* is an HTTP method that won't trigger a preflight request. The simple methods are defined as:

- `GET`
- `HEAD`
- `POST`

Note that requests with a simple method may still trigger a preflight request if they contain nonsimple headers. The next section covers simple headers.

Simple header

A *simple header* is an HTTP request header that won't trigger a preflight request. The client doesn't need the server's permission (via a preflight) to make requests with only these headers. The simple headers are defined as:

- Accept
- Accept-Language
- Content-Language
- Content-Type, but only if the value is one of the following:
  - `application/x-form-urlencoded`
  - `multipart/form-data`
  - `text/plain`