- Internet Explorer 10+
- Opera 12+

In addition to desktop browsers, CORS is fully supported in most mobile browsers, including iOS 3.2+ and Android 2.1+. Mobile devices tend to have up-to-date software, so if you're developing for mobile browsers, you can be comfortable knowing your users have CORS support.

Internet Explorer 8 and 9 support a limited version of CORS using something called the `XDomainRequest` object, which is limited to only certain types of CORS requests. If cross-origin requests in Internet Explorer 8 or Internet Explorer 9 are important to your application, you'll want to learn about the limitations in `XDomainRequest`.

If the browser's version is older than the ones mentioned here, it probably doesn't support CORS. If you need to support cross-origin requests in an older browser, there are still options. As we'll cover in appendix D, there are other mechanisms available for making cross-origin requests in older browsers. But you won't be able to use the techniques described here.

Table 2.1 breaks down the landscape of CORS support in browsers. As of mid-2014, approximately 83% of the browsers out there have full support for CORS, and another 6% have partial support.

Table 2.1 CORS support in browsers

Tier	CORS support	Browsers
1	Full CORS support	Chrome 3+, Firefox 3.5+, Safari 4+, Internet Explorer 10+, Opera 12+
2	Partial CORS support	Internet Explorer 8, Internet Explorer 9
3	No CORS support	Chrome 2 and below, Firefox 3 and below, Safari 3 and below, Internet Explorer 7 and below, Opera 11 and below

(*Source*: http://caniuse.com/#search=cors.)

The next two sections look at how to work with CORS in tier 1 and tier 2 browsers. Tier 1 browsers use the `XMLHttpRequest` object to make cross-origin requests, while tier 2 browsers use the `XDomainRequest` object. Let's start by looking at the `XMLHttpRequest` object.

2.3 Using the XMLHttpRequest object

JavaScript code can make HTTP requests with the `XMLHttpRequest` object. Listing 1.1 showed you how the `XMLHttpRequest` object can be used for a CORS request to the Flickr API. The following listing shows the code from listing 1.1 and highlights the individual pieces of the request.

Listing 2.1 Making a CORS request to the Flickr API

```
<!DOCTYPE html>
<html>
<body onload="loadPhotos();">
```