before, some of this information may still be new, because the `XMLHttpRequest` object underwent a revision around 2010. The latest version has new properties that help enable CORS. The older version of `XMLHttpRequest` works in older tier 3 browsers, but because it doesn't support CORS, it isn't covered here.

2.3.1 Sending an HTTP request

The first step in making an HTTP request is setting up a new `XMLHttpRequest` object. The following listing highlights the code that sets up the request.

Listing 2.2 Setting up an HTTP request to the Flickr API

```
<!DOCTYPE html>
<html>
<body onload="loadPhotos();">
<div id="photos">Loading photos...</div>
<script>
function loadPhotos() {
  var api_key = '<YOUR API KEY HERE>';
  var method = 'GET';
  var url = 'https://api.flickr.com/services/rest/?' +
      'method=flickr.people.getPublicPhotos&' +
      'user_id=32951986%40N05&' +
      'extras=url_q&format=json&nojsoncallback=1&' +
      'api_key=' + api_key;

  var xhr = new XMLHttpRequest();
  if (!('withCredentials' in xhr)) {
    alert('Browser does not support CORS.');
    return;
  }
  xhr.open(method, url);

  xhr.onerror = function() {
    alert('There was an error.');
  };

  xhr.onload = function() {
    var data = JSON.parse(xhr.responseText);
    if (data.stat == 'ok') {
      var photosDiv = document.getElementById('photos');
      photosDiv.innerHTML = '';
      var photos = data.photos.photo;
      for (var i = 0; i < photos.length; i++) {
        var img = document.createElement('img');
        img.src = photos[i].url_q;
        photosDiv.appendChild(img);
      }
    } else {
      alert(data.message);
    }
  };

  xhr.send();
}
```

Defines HTTP method and URL

Creates new XMLHttpRequest object

Assigns HTTP method and URL to XMLHttpRequest object