requests can include any custom request header. If the server doesn't whitelist the request headers, the request will fail. We'll dive into more details on how a server does this in chapter 4.

MAKING THE REQUEST

Once the request is set up, calling the `send` method will send the HTTP request to the server, as shown in the following listing.

Listing 2.3 Calling the `send` method to initiate the HTTP request

```
<!DOCTYPE html>
<html>
<body onload="loadPhotos();">
<div id="photos">Loading photos...</div>
<script>
function loadPhotos() {
  var api_key = '<YOUR API KEY HERE>';
  var method = 'GET';
  var url = 'https://api.flickr.com/services/rest/?' +
      'method=flickr.people.getPublicPhotos&' +
      'user_id=32951986%40N05&' +
      'extras=url_q&format=json&nojsoncallback=1&' +
      'api_key=' + api_key;

  var xhr = new XMLHttpRequest();
  if (!('withCredentials' in xhr)) {
    alert('Browser does not support CORS.');
    return;
  }
  xhr.open(method, url);

  xhr.onerror = function() {
    alert('There was an error.');
  };

  xhr.onload = function() {
    var data = JSON.parse(xhr.responseText);
    if (data.stat == 'ok') {
      var photosDiv = document.getElementById('photos');
      photosDiv.innerHTML = '';
      var photos = data.photos.photo;
      for (var i = 0; i < photos.length; i++) {
        var img = document.createElement('img');
        img.src = photos[i].url_q;
        photosDiv.appendChild(img);
      }
    } else {
      alert(data.message);
    }
  };

  xhr.send();
}
</script>
</body>
</html>
```

The send method initiates the HTTP request.