```
        replay1 = add_to_replay(replay1, obs_small_1,
        acts_1,rewards1,act_means1,qnext1)
1
        replay2 = add_to_replay(replay2, obs_small_2,
        acts_2,rewards2,act_means2,qnext2)
        shuffle(replay1)
2
        shuffle(replay2)

        ids_1_ = list(zip(np.arange(ids_1.shape[0]),ids_1))
3
        ids_2_ = list(zip(np.arange(ids_2.shape[0]),ids_2))

        env.clear_dead()
4

        ids_1  = env.get_agent_id(team1)
5
        ids_2  = env.get_agent_id(team2)

        ids_1_ = [i for (i,j) in ids_1_ if j in ids_1]
6
        ids_2_ = [i for (i,j) in ids_2_ if j in ids_2]

        acts_1 = acts_1[ids_1_]
7
        acts_2 = acts_2[ids_2_]

        step_ct += 1
        if step_ct > 250:
            break

        if len(replay1) > batch_size and len(replay2) > batch_size:
8
            loss1 =
train(batch_size,replay1,params[0],layers=layers,J=N1)
            loss2 =
train(batch_size,replay2,params[1],layers=layers,J=N1)
            losses1.append(loss1)
            losses2.append(loss2)
```

- ***1*** Adds to experience replay
- ***2*** Shuffles the replay buffer
- ***3*** Builds a zipped list of IDs to keep track of which agents died and will be cleared from the grid
- ***4*** Clears the dead agents off the grid
- ***5*** Now that the dead agents are cleared, gets the new list of agent IDs
- ***6*** Subsets the old list of IDs based on which agents are still alive