```
B1QDOH//AWhRYAQ=
```

This Base64 string decodes to 11 hex bytes as follows:

```
07 54 03 38 7f ff 01 68 51 60 04
```

> ***NOTE***
>
> Base64 is a way to represent binary data (like images, files, or any non-text data) using only text characters that are safe to use anywhere—specifically 64 different characters: A-Z, a-z, 0-9, plus two symbols (usually + and /).

According to the device manual, these 11 bytes contain measured temperature and humidity in the first 4 bytes, followed by data from an optional external temperature probe and the measurement timestamp as shown in table 3.5.

Table 3.5 Format of the message received from a Dragino LHT52 indoor LoRaWAN temperature and humidity sensor.

Bytes	Size	Content	Format
0-1	2	Temperature	Signed 16-bit, ÷100
2-3	2	Humidity	Unsigned 16-bit, ÷10
4-5	2	External Temperature	Signed 16-bit, ÷100
6	1	External Sensor ID	Unsigned 8-bit
7-10	4	Unix timestamp	Unsigned 32-bit

The first 2 bytes `0x07 0x54` represent a signed 16-bit temperature value (signed means it can represent temperatures both above and below 0°C, though it never gets below freezing where I live!). Decoding requires bit manipulation as shown in the function shown in listing 3.4.