Listing 5.2 A minimal example of how a room might be defined using the Digital Twin Definition Language.

```
{
  "@id": "dtmi:com:dtia:Room;1", #1
  "@type": "Interface", #2
  "displayName": "Room",
  "contents": [
    {
      "@type": "Property",
      "name": "occupancyStatus",
      "displayName": "Occupancy Status",
      "schema": "boolean"
    },
    {
      "@type": "Telemetry",
      "name": "temperature",
      "displayName": "Temperature",
      "schema": "double"
    }
  ],
  "@context": "dtmi:dtdl:context;3" #3
}
```

#1 The @id attribute defines a unique identifier for the entity.
#2 The @type attribute specifies what kind of thing this data represents.
#3 The @context attribute is a link to a vocabulary that defines what terms mean - the DTDL version 3 context file.

5.3.3 Choosing an ontology for your model

There are many ontologies defined for a variety of domains, for example Microsoft has defined a number of industry standard ontologies specifically for digital twins using the DTDL. When considering the ontology you will adopt in your digital twin's model, you can adopt one of several strategies:

1. Adopt an existing standard ontology if one exists for your domain. The benefit of this approach is interoperability with other systems that use the same standard, combined with proven concepts that are likely supported by existing tools. The main drawback here is that the rigidity of defined standards may not fit your specific needs perfectly, limiting your ability to innovate.