Note that the {% url %} tag returns relative URLs. This isn't a problem on a website, as the browser takes care of sending you to the right site. In an email, this is problematic, though, so you must include the protocol and domain in the link. The view includes this information in the context dictionary; you just need to render it. Using the console backend for development, you get the following email info:

```
Content-Type: text/plain; charset="utf-8"
MIME-Version: 1.0
Content-Transfer-Encoding: 7bit
Subject: Password reset on 127.0.0.1:8000
From: webmaster@localhost
To: admin@example.com
Date: Tue, 02 May 2023 18:54:52 -0000


  You're receiving this email because you requested a password reset
  for your user account at RiffMates.

  Please go to the following page and choose a new password:


    http://127.0.0.1:8000/accounts/reset/MQ/bnl5vg-f639/


  Your username, in case you've forgotten: admin

  Thanks for using our site!
```

6.6.3 New password form

The next step in the reset process happens when the user clicks the one-time link in the email message. The link leads to a view that shows a form for entering a new password. This form uses the standard enter-it and then enter-it-to-confirm mechanism. The associated template is password_reset_confirm.html. Add the contents of the following listing to RiffMates/templates/registration/password_reset_confirm.html.

Listing 6.12 Template where the user chooses a new password

```
{% extends "base.html" %}

{% block content %}

{% if validlink %}
  <form method="post">
    {% csrf_token %}
    {{ form.as_p }}

    <input type="submit" value="Change password">
  </form>
{% else %}
  <p>
    Invalid password reset link!
```