venue (which does require a URL argument). Don't forget to name the routes, as you'll want to link to them later.

Listing 7.18 The self-service view for adding and editing venues

```
# RiffMates/bands/views.py
...
from django.shortcuts import render, get_object_or_404, redirect

from bands.models import Musician, Band, Venue, Room
from bands.forms import VenueForm
...
@login_required
def edit_venue(request, venue_id=0):
    if venue_id != 0:
        venue = get_object_or_404(Venue,
            id=venue_id)
        if not request.user.userprofile.venues_controlled.filter(
                id=venue_id).exists():
            raise Http404("Can only edit controlled venues")

    if request.method == 'GET':
        if venue_id == 0:
            form = VenueForm()
        else:
            form = VenueForm(instance=venue)

    else: # POST
        if venue_id == 0:
            venue = Venue.objects.create()

        form = VenueForm(request.POST, request.FILES,
            instance=venue)

        if form.is_valid():
            venue = form.save()

            # Add the venue to the user's profile
            request.user.userprofile.venues_controlled.add(venue)
            return redirect("venues")

    # Was a GET, or Form was not valid
    data = {
        "form": form,
    }

    return render(request, "edit_venue.html", data)
```

This is the edit case.

Check if the requested Venue object is part of the user's venues_controlled relationship. If not, raise a 404 error.

Fetch the requested Venue object.

The GET portion is the same as other form processing views.

In the add case, create a new, empty Venue object to associate with the form.

Include request.FILES in form creation to get both the form's fields and the uploaded file.

Add the (possibly new) venue to the user's venues_controlled relationship. The .add() method handles the case where the relationship already exists.

Of course, you'll need a template to go with this view. Listing 7.19 shows the contents of the new RiffMates/templates/edit_venue.html file. This file is almost identical to the classified ad form-handling template, with one exception. To handle files, the `<form>` tag needs an additional argument: `enctype="multipart/form-data"`. Without this, the upload won't work properly, and this can be a painful bug to find.