`list` vs. `List`

The code in this book was written and tested with Python 3.12. Type hinting with built-in types got introduced in Python 3.9. If you're using Python 3.8 or earlier, the endpoint function declaration needs the `List` class from the `typing` module instead. It looks like this:

```
from typing import List

@router.get("/promoters/",
        response=List[PromoterSchema])
def promoters(request):
    return Promoter.objects.all()
```

Note the use of List instead of list.

As this is a new file with a new `Router` object in it, you need to register it with the `NinjaAPI` object in urls.py. The following listing highlights the changes needed there.

Listing 11.5 Register the `Router` for the `promoters` app

```
# RiffMates/RiffMates/urls.py
...
from promoters.api import router as promoters_router
...
api = NinjaAPI(version="1.0")
api.add_router("/home/", home_router)
api.add_router("/promoters/", promoters_router)
...
```

Import the promoters Router object with an alias.

Register the new router with the NinjaAPI object.

Note that you don't need to make changes to the `path` object; using the `add_router()` call is sufficient. Depending on how much playing around you did in chapter 10, you may or may not have promoter data in your database. Make sure you do, or your API won't have anything to return. You can either use the Django Admin to add some information, or for your convenience, the sample code has a fixture starting in the ch10g_exercises directory. Note that this fixture pairs with the changes in the chapter 10 exercises and will only work if you model matches that work.

Your new endpoint is http://localhost:8000/api/v1/promoters/promoters; visit it to see the results. The double noun of `promoters/promoters` is a little annoying but common practice. The first noun is the namespace, and the second indicates this is listing a series of objects. For the `promoters` app, this is overkill: there is only one model inside it. When you start building the APIs for bands, musicians, and venues, this kind of namespacing becomes important. Your results should look something like this:

```
[{
    "id": 1,
    "full_name": "Michael Lang",
    "birth": "1944-12-11",
    "death": "2022-01-08"
},
```