```
        hx-trigger="load">
    <i> Loading promoters... </i>
  </div>
{% endblock content %}
```

hx-trigger specifies when the GET occurs—in this case, on page load.

Placeholder text visible until the lazy load completes

The `hx-get` tag fires when the page loads and calls the associated URL. The following listing contains the view this GET invokes.

**Listing 12.3 An HTMX-invoked promoters listing view**

```
# RiffMates/promoters/views.py
from time import sleep
...
def partial_promoters(request):
    sleep(2)
    data = {
        "promoters": Promoter.objects.all(),
    }
    return render(request, "partials/promoters.html",
        data)
```

A two-second delay to simulate lazy loading taking a while

HTMX results get rendered the same as any other template, but the contents are only a partial page.

The following listing contains the partial HTML segment, rendered by the `partial_promoters()` view. I keep all my partials together in a subdirectory, created under templates. This first partial is named RiffMates/templates/partials/promoters.html.

**Listing 12.4 A snippet of HTML that gets rendered in response to an HTMX GET call**

```
<!-- RiffMates/templates/partials/promoters.html -->
<ul>
  {% for promoter in promoters %}
    <li>
      {{promoter.full_name}}
      {% if promoter.birth %}
        (
          {{promoter.birth}} -
          {% if promoter.death %}
            {{promoter.death}}
          {% endif %}
        )
      {% endif %}
    </li>
  {% empty %}
    <li> <i>No promoters in the database</i> </li>
  {% endfor %}
</ul>
```

Loop through all promoters.

Render each promoter as a list item.

An alternate message if there are no promoters

To test all this out, you need to add a urls.py file to the `promoters` app, register the two new views, and include the URL routes in the main RiffMates/urls.py file. You'll also need some promoters if you haven't created them already. You can do this with the