The trigger also supports additional parameters. Using `"keyup changed delay:500ms"` adds a filter to the trigger. Now, only key releases that change the value of the field invoke the GET. Pressing an arrow key won't cause the trigger. The `delay` tells HTMX to wait until typing has stopped, or at least paused. The trigger doesn't activate until 500 milliseconds after the last keypress. If the user is typing quickly, the page waits a bit before invoking the trigger, so as not to overwhelm the server.

Search results get inserted in a `<div>` tag on the page. The `<div>` has an ID, which the `<input>` tag targets with an `hx-target` attribute. The GET call's results get inserted into the target tag.

HTMX allows you to tie the content of the input box to the browser's URL by using the `hx-push-url` attribute. With this attribute set to `"true"`, anything the user types in gets appended to a query parameter in the URL. This allows for deep linking. You can copy and paste the URL into another window to perform the same search results. This also means your search can be bookmarked. Because of this, the initial rendering of the page may need to include search results, but you don't need to use HTMX for this—you can instead include it as part of the page rendering like with non-HTMX views. The `<div>` tag where results go starts with rendering any initial results and is the target for any appended results. As this chunk of HTML is needed in two places (the initial and update calls), I've encapsulated it into its own file, so it can be included by the template engine. The following listing contains the main search page.

Listing 12.7 The template for the search page

```
<!-- RiffMates/templates/search_musicians.html -->
{% extends "base.html" %}

{% block content %}
  <h1>Search Musicians</h1>

  <input name="search_text"
    placeholder="Search for musicians..."
    type="text"
    value="{{search_text}}"
    hx-get="{% url 'search_musicians' %}"
    hx-trigger="keyup changed delay:500ms"
    hx-target="#results"
    hx-push-url="true">

    <div class="results" id="results">
      {% include "partials/musician_results.html" %}
    </div>
{% endblock content %}
```

The URL to call when the search terms change

The input box for search terms

When the page is deep-linked, render the search terms in the input box.

Trigger a GET when a keyup event changes the content of the input box.

Returned results get rendered in the tag matching this CSS query selector.

Turning on hx-push-url causes the URL's search_text query parameter to be updated with the contents of the input box.

The parent tag for any results

The partial HTML segment that renders the resulting list of musicians

The subtemplate that both gets included by the search page and used as a partial HTML result is shown in the following listing.