```
def search_musicians(request):
    ...

    # Query results are in the "musicians" object by this point in the code

    items_per_page = _get_items_per_page(request)
    paginator = Paginator(musicians, items_per_page)
    page_num = _get_page_num(request, paginator)
    page = paginator.page(page_num)

    data = {
        "search_text": search_text,
        "musicians": page.object_list,
        "has_more": page.has_next(),
        "next_page": page_num + 1,
    }

    if request.htmx:
        if page_num > 1:
            sleep(2)

        return render(request, "partials/musicians_results.html", data)

    return render(request, "search_musicians.html", data)
```

Paginate the results of the search.

"musicians" now contains only this page of results.

True if there is more data

The value of the next page of data

If you are rendering after the first page, wait 2 seconds.

You'll note that like with the promoters partial view, I've included a time delay in this code. On your local machine, using a development server, it can be hard to see the call for the next data, as it happens so fast. To help check things are working properly, I've intentionally made the call take at least 2 seconds.

The search view now supports pages of data. To add infinite scrolling, you need an HTMX trigger for when a tag scrolls into view. This trigger value is `"revealed"`. At the bottom of the results page, insert a `<div>` that calls the next page of results when it gets revealed on the page. Of course, `<div>` tags are invisible, so the user doesn't see anything, but the browser doesn't care. The tag is either within the browser's view port, or it is not, and the first time it "shows" in the view port, the HTMX call gets triggered. Add the code in the following listing to the bottom of RiffMates/templates/partials/musician_results.html.

Listing 12.11 The inner template for the search results

```
<!-- RiffMates/templates/partials/musician_results.html -->
<!-- ... -->

{% if has_more %}
  <div
    hx-get="{% url 'search_musicians' %}?page={{next_page}}
    ➥ &search_text={{search_text}}"
    hx-trigger="revealed"
```

The view sets has_more to True if there are more pages of data.

GET invokes the same search view with query parameters specifying the next page number and the search text.

Trigger the HTMX call when this tag becomes visible on screen.