- The `hx-target` and `hx-swap` attributes control what parts of a page get modified when an action gets invoked. The target uses a CSS selector to determine what tag gets replaced, while the swap attribute determines which part of the tag changes.
- Lazy loading allows you to add content to the page after it has been displayed and is typically used for assets that take a long time to be generated or downloaded.
- To build lazy loading with HTMX, you use the `hx-trigger` attribute, set to a value of `"load"`, along with an `hx-get`, pointing to the URL of the asset to be fetched.
- Since HTMX uses HTTP methods, the Django portion of the code can be the same kinds of views you've written before.
- HTMX sets a header to indicate a call invoked by the library; this allows you to write views that serve both the full page and the replacement segment for an HTMX call.
- The segments of HTML returned in response to an HTMX call are known as *partials*.
- HTMX appends the contents of input boxes onto an `hx-get` URL as a query parameter.
- Search-as-you-type is a feature that populates search results dynamically as the user enters search terms in an input box.
- To build search-as-you-type in HTMX, you combine an input box with an `hx-get` call to the search view. An `hx-trigger` based on the `keyup` event invokes the GET when a key is pressed and released.
- When using an `hx-triggerkeyup` event, you can filter events with `changed`, so only keypresses that change an input box's value invoke the GET call.
- The `django.db.models.Q` object allows you to create arbitrarily complex ORM queries, using both AND and OR terms.
- Infinite scroll is a feature that adds additional data to the page when the user scrolls to the bottom.
- You can implement infinite scroll in HTMX by using the `hx-trigger` attribute with a value of `revealed`. When the tag scrolls onto screen, it triggers a GET call to fetch more content.
- Infinite scroll in Django is best handled using a `Paginator` class, with a page of data returned for each invocation of the associated view.
- The `django-htmx` library provides a middleware component, which can be used to test whether the view got called by HTMX or a regular page view.
- Click-to-edit is a feature displaying data as well as a button or link, which, when clicked, changes the display data into an edit form.
- You implement click-to-edit with HTMX by using `hx-get` to change viewable data into a form and `hx-post` to submit the form. This can be combined with an additional `hx-get` to cancel out of the edit.