Table C.1 Built-in Django template tags

Tag	Description
`{% csrf_token %}`	This tag is part of Django's cross-site request forgery (CSRF) protection and should be included in any forms.
`{% cycle "red" "blue" %}`	Each time this tag is called, it produces its next listed argument. When the list is exhausted, it resumes from the start. It is typically used inside a `{% for %}` tag, changing its value on each iteration. One common use is creating a zebra-stripe effect by changing the style of an `<li>` element or the class of a `<tr>`.
`{% debug %}`	This outputs a large amount of debug information, including text component parts of the page, user information, and every loaded module. It only works if you have `DEBUG=True` in settings.py.
`{% extends "base.html" %}`	Part of the template inheritance mechanism, `{% extends %}` is used at the top of a file to indicate a template is a child of the named template, `"base.html"` in the example. Any `{% block %}` tags in this instance will override `{% block %}` tags of the same name in the parent.

`{% filter force_escape|lower %}`
`  This content will have the named`
`filters applied before rendering`
`{% endfilter %}`
	This allows the use of one or more filters on the body of the tag. Filters to be applied are named as arguments; multiple filters can be applied through the use of the pipe (`|`).

`{% firstof is_leapyear is_winter is_week` `day "default" %}`	This outputs the value of the first value in its list that is not false-y, where *not false-y* means *it exists, is not empty, is not* `False`*, and is greater than zero if numeric*. A final string value can be provided to force a default result (all nonempty strings are `True`).

`{% for person in people %}`
`  {{ person.name }}`
`{% empty %}`
`  <i> No people </i>`
`{% endfor %}`
	This is the template equivalent of a Python `for` statement, and it loops over an iterable (`people`) and places the current instance in a value (`person`). The optional `{% empty %}` clause is run if the iterable is empty.

`{{ forloop.counter }}`
`{{ forloop.counter0 }}`
`{{ forloop.revcounter }}`
`{{ forloop.revcounter0 }}`
`{{ forloop.first }}`
`{{ forloop.last }}`
`{{ forloop.parentloop }}`
	These values are defined within the context of a `{% for %}` block, giving information on the current state of the loop. They correspond to the current count (1-based), current count (0-based), number of iterations from the end (1-based), number of iterations from the end (0-based), `True` if the first iteration, `True` if the last iteration, and the context value of a parent loop in the case of nested `{% for %}` tags. For a nested `{% for %}` tag, `{{ forloop.parentloop.counter }}` contains the counter of the parent loop.