Table C.1 Built-in Django template tags *(continued)*

Tag	Description

`{% if count > 50 %}`
`  It is big`
`{% elif count > 20 %}`
`  It is medium`
`{% else %}`
`  It is small`
`{% endif %}`
	This is the template equivalent of a Python `if` statement. The Boolean condition supports `and`, `or`, `not`, `==`, `!=`, `<`, `?`, `>`, `>=`, `in`, `not in`, `is`, and `is not` operators. Values in the condition support the use of filters through the pipe (`|`) operator and can be grouped with parentheses.

`{% ifchanged minute %}`
`  More than a minute went by`
`{% else %}`
`  Less than a minute went by`
`{% endifchanged %}`
	This checks whether a value has changed since the last time the same tag was executed. It is used within a `{% for %}` tag to determine if a value is different on a subsequent iteration. The `{% else %}` tag is optional.

`{% include "subtemplate.html" %}`
or
`{% include "subtemplate.html" with name="Connor" %}`
	This loads and renders a subtemplate. Using `with` sets values within the subtemplate's context.

`{% load taglibrary %}`	This loads a custom tag/filter library for use. It is equivalent to a Python `import` statement.
`{% lorem 10 w %}`	This outputs placeholder text, using the traditional "lorem ipsum" text. Arguments are optional, specifying the amount of content, the type of content (`w` for words, `p` for HTML paragraphs, and `b` for plain-text paragraph blocks), and the word `random` to generate random text instead of lorem ipsum.
`{% now "Y/m/d" %}`	This outputs the current date, using the specified format. This example outputs the date in ISO 8601 format, such as `"1999/12/25"`. Date string specifiers can be found here: https://docs.djangoproject.com/en/dev/ref/templates/builtins/#std-templatefilter-date
`{% regroup value by key as result %}`	This takes a list of dictionaries (`value`) and creates a new list, where items with the same key are grouped together. For example, if `value` contained a list of dictionaries with city information, where each city had a key named `country`, regrouping on `country` creates a new list, containing a nested list for each unique country found.
`{% resetcycle %}`	This resets a previous cycle tag so that it begins at the start of its argument list again. It is typically used in nested `{% for %}` tags, so the inner `{% for %}` starts at the beginning of a cycle rather than the state from the previous iteration.

`{% spaceless %}`
`  <p>`
`  <b>This is some content</b>`
`  </p>`
`{% endspaceless %}`
	This removes whitespace (including newlines) *between* HTML tags. Note that it does not remove spaces *within* HTML tags. The example renders as `<p><b>This is some content</b></p>`.