Table C.2 Loadable Django tags *(continued)*

Tag	Module	Description

`{% blocktranslate %}`
`  A translated string with a {{ value }}.`
`{% endblocktranslate %}`
	i18n	This returns the translated text equivalent looked up within the translation files. It supports bound variables for look-up within the translation system.

`{% get_available_languages %}`	i18n	This returns a list of available languages from the translation system. The list contains tuples pairing the language code with the name of the language.
`{% get_current_language %}`	i18n	This returns the current language as a language code based on the user's preferred value.
`{% get_current_language_bidi %}`	i18n	This returns the current language's rendering direction—`True` for right-to-left languages.
`{% get_language_info for "en-ca" as lang %}`	i18n	This puts language information for the named code (`"en-ca"`) in the value (`lang`). Language information is an object with attributes for the language code (`lang.code`), language name (`lang.name_local`), language name in English (`lang.name`), language bi-direction (`lang.bidi`), and name in the active language (`lang.name_translated`).
`{% get_language_info_list for` `  available_langs as langs %}`	i18n	This creates a list (`langs`) of language info data structures for each language code in the `available_langs` iterable.

`{% localize on %}`
`  {{ value }}`
`{% endlocalize %}`
	l10n	This activates (`on`) or deactivates (`off`) localization within the block contents.

`{% localtime on %}`
`  {{ value }}`
`{% endlocaltime %}`
	tz	This activates (`on`) or deactivates (`off`) conversion of aware datetime objects contained within the block to the current time zone.

`{% timezone "America/Toronto" %}`
`  {{ value }}`
`{% endlocaltime %}`
	tz	This converts any datetime objects contained within the block to the named time zone.

`{% get_current_timezone as my_zone %}`	tz	This puts the name of the current time zone in the named argument (`my_zone`).