Table C.3 Built-in Django template filters *(continued)*

Filter	Description
`{{ value|floatformat }}` or `{{ value|floatformat:3 }}` or `{{ value|floatformat:"-3" }}` or `{{ value|floatformat:"3g" }}` or `{{ value|floatformat:"3u" }}`	This formats float values. With no argument, it displays a single decimal place. Integer arguments specify the number of decimal places. String arguments are converted to integers. Negative arguments specify the number of decimal places but show an integer if the number is precise (e.g., `7.1` becomes `7.100`, while `7.0` becomes `7`). A `g` suffix adds a thousandths separator. A `u` suffix turns localization off.
`{{ value|force_escape }}`	This performs HTML escaping on `value`, even if it has already been escaped.
`{{ value|get_digit:"2" }}`	This returns the nth digit of an integer from the right.
`{{ value|iriencode }}`	This converts an Internationalized Resource Identifier (IRI) to a string that can be included in a URL.
`{{ value|join:"," }}`	This returns a string composed of all the elements in a list, putting the argument between each item. It is equivalent to Python's `str.join()`.
`{{ value|json_script:"my-id" }}`	This converts a Python object to JSON wrapped in a `<script>` tag. The tag will have an `id` attribute corresponding to the argument.
`{{ value|last }}`	This returns the last item in a list.
`{{ value|length }}`	This returns the length of a string or list.
`{{ value|linebreaks }}`	This converts plain text into a paragraph, wrapping the content with `<p>` and `</p>` tags. A single newline within the content is converted to a ` `, while double newlines are converted into a second set of paragraph tags.
`{{ value|linebreaksbr }}`	This replaces newlines in a string with HTML ` ` tags.
`{{ value|linenumbers }}`	This prefixes each line in `value` with a line number.
`{{ value|ljust:"15" }}`	This adds whitespace to left justify the contents for the given width. Note: this is only visible in HTML inside certain tags, as HTML normally ignores whitespace.
`{{ value|lower }}`	This converts all characters to lowercase.
`{{ value|make_list }}`	This converts `value` into a list. For strings, the characters become items in the list; for integers, the digits become their character equivalents in the list.
`{{ value|phone2numeric }}`	This converts a phone number containing letters to its numeric equivalent. It does not validate the format of the phone number.