Table D.2 ORM field types

Field	Description
`FileField(upload_to="", storage=None, max_lenth=100, **options)`	This stores the path to a file that was uploaded. The `upload_to` argument indicates the directory for uploading. The `storage` argument indicates the object that handles file storage; if `None`, the default Django storage mechanism is used. Full details on storage objects are available in the documentation: https://docs.djangoproject.com/en/dev/topics/files/#storage-objects. The `max_length` argument restricts the length of the filename. Instances of this field have attributes that contain more information about the file: `.name` is the file name, `.path` is the file path, `.size` is the file size, and `.url` is the URL used to access the file. Field instances also support several methods—`.open()`, `.close()`, `.save()`, and `.delete()`— which correspond to the equivalent file operations.
`FilePathField(path="", match=None, recursive=False, allow_files=True, allow_folders=False, max_lenth=100, **options)`	This is a `CharField`, whose choices are restricted to the names of files at a given path. The `path` argument is required and points to the directory used to inspect for allowable values. All other arguments are optional. The `match` argument can contain a regular expression to restricts the names of the paths. Set `recursive` to `True` to include subdirectories. Values for `allow_files` and `allow_folders` incidate whether file and directory paths are included as possible values.
`FloatField(**options)`	Stores a floating point number.
`GenericIPAddressField(protocol="both", unpack_ipv4=False, **options)`	Stores an IPv4 or IPv6 IP address as a string. The `protocol` argument can be one of `both`, `IPv4`, or `IPv6`. Setting `protocol` to `IPv4` or `IPv6` restrict the field to that kind of address. When `protocol` is `both` and `unpack_ipv4` is `True`, packed IP4 addresses are unpacked when accessed (e.g., `::ffff:192.0.2.1` becomes `192.0.2.1`).
`ImageField(upload_to=None, height_field=None, width_field=None max_length=100, **options)`	An instance of a `FileField` that validates the uploaded file is an image. It requires the Pillow library to be installed. The `height_field` and `width_field` arguments optionally name other fields in the table that get automatically updated with the image's height and width values.