```
        "version": "0.0.1",
    }

    return JsonResponse(data)
```

The JsonResponse object takes data to be serialized and sets the correct MIME type for JSON content.

As with all views, Version Info must be registered against a URL. This is shown in the following listing.

Listing E.4 Register the Version Info view as a route

```
# RiffMates/RiffMates/urls.py
...
from home import views as home_views

urlpatterns = [
    # ...
    path("version/", home_views.version),
    # ...
]
```

E.2 Chapter 3

In chapter 3 you learned about Django's template engine, including how to use tags and filters, as well as how Django escapes content to make it safe to render in HTML.

Exercise 1

Create a new base HTML file, using your favorite web-style framework, such as Bootstrap or Tailwind. Once you have something pretty, test it out by changing news2.html to extend from it.

Django's template engine allows you to compose templates together to promote re-use of HTML or any other text content. One of these re-use mechanisms is inheritance. As HTML is quite verbose, writing a good base file to inherit from once means your individual pages can be quite small.

The following listing contains the top part of the content from a base HTML page that uses the Bootstrap 5 framework.

Listing E.5 Declaration and head part of a base HTML file

```
<!-- RiffMates/templates/base_bootstrap.html -->
<!doctype html>
<html lang="en" class="h-100">
<head>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <meta name="description" content="">
  <title>
    {% block title %}
```

Putting the page's title in a block allows it to be overridden by child pages.