The last portion of the new base file contains a block for page content, a footer, and the JavaScript expected by the Bootstrap framework. Combine the following listing with the other three parts to create your new base file.

Listing E.7 The section where main content gets rendered

```
<!-- Begin page content -->
<main class="flex-shrink-0">
  <div class="container">
    {% block content %}
    {% endblock content %}
  </div>
</main>

<footer class="footer mt-auto py-3 bg-light">
  <div class="container">
    {% block footer %}
      <span class="text-muted">RiffMates: by musicians for musicians</span>
    {% endblock footer %}
  </div>
</footer>

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha1/dist/js/
➥ bootstrap.bundle.min.js" integrity="sha384-w76AqPfDkMBDXo30jS1Sgez6pr
➥ 3x5MlQ1ZAGC+nuZB+EYdgRZgiwxhTBTkF7CXvN" crossorigin="anonymous">
➥ </script>

</body>
</html>
```

This empty block is where page content goes in inheriting files.

Putting the footer in its own block allows the content to be overridden or added to in child pages.

With the new base_boostrap.html file in place, you can take advantage of the sexier look by inheriting from it. To try it out, modify the news2.html file, changing the `extends` statement to use your new base file. The result is shown in the following listing.

Listing E.8 Modified news2.html file using the Bootstrap base template

```
<!-- RiffMates/templates/news2.html -->
{% extends "base_bootstrap.html" %}

{% block title %}
  {{block.super}}: News
{% endblock %}

{% block content %}
  <h1>RiffMates News (2)</h1>

  <ul>
    {% for item in news %}
      <li>{{ item }}</li>
    {% endfor %}
  </ul>

{% endblock content %}
```

Changing the extends tag is all that is required to change where this template is inherited from.