```
  },
  "highlight": {
    "fields": {
      "title": {}
    }
  }
}
```

The highlight block lets us visualize the results.

The output shows us that two movies matched:

```
"title": [ "The <em>Good</em>, the Bad and the Ugly" ]
"title": [ "City of <em>God</em>"]
```

We use the `?` wildcard only if we want to match one character. For example, `"value": "go?ather"` searches for all the words that match the third character at the wildcard's position. We can also combine multiple `?` characters, such as "g???ather".

Expensive queries

Some queries are expensive for the engine to run because of how we implement them. The `wildcard` query is one, along with `range`, `prefix`, `fuzzy`, `regex`, and `join` queries. Using such a query occasionally may not impact server performance, but overusing these expensive queries may destabilize the cluster, leading to bad user experiences.

Elasticsearch allows us to execute expensive queries on the cluster at our discretion. However, if we want to stop the execution of these queries on the cluster, we can set the `allow_expensive_queries` attribute to `false` on the cluster settings:

```
PUT _cluster/settings
{
  "transient": {
    "search.allow_expensive_queries": "false"
  }
}
```

By switching off `allow_expensive_queries`, we protect the cluster from overload.

Note that if we set `allow_expensive_queries` to `false`, `wildcard` queries are not executed. The following error is thrown if we try: `"reason" : "[wildcard] queries cannot be executed when 'search.allow_expensive_queries' is set to false."`

Wildcards fetch results with missing characters in a word or a sentence. Sometimes we wish to query words with a prefix—that's when `prefix` queries come into the picture, as discussed next.

9.8 The prefix query

We may want to query for words using the beginning of a word (a prefix), like *Leo* for Leonardo or *Mar* for Marlon Brando, Mark Hamill, or Martin Balsam. We can use `prefix` queries to fetch records that match the prefix, as shown in the following listing.