```
      }
    }
  },
  "highlight": {
    "fields": {
      "actors.original": {}
    }
  }
}
```

Highlights the matched actors in the results

Because we don't want the source to be returned in the response (`"_source": false`), the following results highlight where the prefix matched with the word:

```
"hits" : [{
   ..
   "highlight" : {
     "actors.original" : ["<em>Marlon Brando</em>"]
   }
 },
 {
   ..
   "highlight" : {
     "actors.original" : ["<em>Martin Balsam</em>"]
   }
 },
 {
   ..
   "highlight" : {
     "actors.original" : ["<em>Mark Hamill</em>"]
   }
 }]
```

We mentioned earlier that running `prefix` queries exerts computation strain. Fortunately, there is a way to speed up such painstakingly ill-performant queries.

9.8.2 Speeding up prefix queries

A `prefix` query is slow to run because the engine must derive results based on a prefix (any lettered word). But there's a mechanism to speed them up: using the `index_prefixes` parameter on the field.

We can set `index_prefixes` when developing the mapping schema. For example, the mapping definition in the following listing sets the `title` field (remember, `title` is a `text` data type) with an additional parameter, `index_prefixes`, on a new index (`boxoffice_hit_movies`) that we are creating for this exercise.

Listing 9.20 New index with the `index_prefixes` parameter

```
PUT boxoffice_hit_movies
{
  "mappings": {
    "properties": {
      "title":{
```

Creates a new index with just one property, title