```
            }
          }
        }
      ],
      "filter": [{
          "range": {
            "gross_earnings_in_millions": {
              "lt": 100
            }
          }
        }
      ]
    }
  }
}
```

Earning shouldn't fall below $100 million

The query uses complex query logic called a `bool` query that combines multiple smaller queries to work on a grand scale. Chapter 12 is dedicated to `bool` queries and digs deeper into how we can construct complicated queries.

5.5.4 Deleting all documents

WARNING Delete operations are irreversible! Be cautious before hitting Elasticsearch with a delete query.

You can delete a whole set of documents from an index using the `match_all` query.

Listing 5.39 Deleting all documents at once

```
POST movies/_delete_by_query
{
  "query": {
    "match_all": {}
  }
}
```

This code runs a `match_all` query. It matches all documents and deletes them simultaneously. This is a destructive operation, so be careful when deleting an entire set of documents! We can also delete the entire index by issuing the `DELETE movies` command—but remember, these are irreversible commands.

So far, we have deleted documents on a single index. We can also delete documents across multiple indexes by simply providing a comma-separated list of indexes in the API URL. The example format is shown here:

```
POST <index_1>,<index_2>,<index_3>/_delete_by_query
```

The following listing deletes all documents across multiple movie-related indexes. Note that we can use `GET _cat/indices` to list all indexes.