```
      "title":{
        "type": "text",
        "fields": {
          "raw":{
            "type":"keyword"
          }
        }
      }
    }
  }
}
```

Defines the title.raw field as a keyword type

In addition to declaring the `title` field as `text` type, we also declare it as a `keyword` type under the name `title.raw`. This way, when we index the document, the `title` field is stored both as a `text` type (thus undergoing text analysis) and as a `keyword` type (with no text analysis). The search can be carried over the `title.raw` field (`keyword` type) to avoid analysis. The following listing shows this; we also index a sample doc before running the query.

Listing 15.6 A `match` query to minimize analysis overhead

```
PUT programming_books3/_doc/1
{
  "title":"Elasticsearch in Action"
}

GET programming_books3/_search
{
  "query": {
    "match": {
      "title.raw": "Elasticsearch in Action"
    }
  }
}
```

Indexes a sample book

Searches on a keyword field

Because we run the search against the `keyword` field, we have to make sure the `title.raw` value is spelled exactly like what was indexed. We cannot fetch the results if even a single letter is different from the original (for example, if the first letter is lowercase). Try the same query again, but this time with lowercase "elasticsearch". You will not receive any results.

There are a few other general recommendations such as using search filters, preindexing data, avoiding wildcard queries, and so on. Consult the official documentation for details: http://mng.bz/MBwm.

Whereas slower search speed impacts search-related performance, slower ingestion speed affects the write part of the application. We discuss these indexing speed problems in the following section.