If you are curious, the Hindi sentence in this example translates to "what are you doing?"

The output from the script is shown here:

```
"tokens" : [{
  "token" : "कैसी",
  "start_offset" : 3,
  "end_offset" : 7,
  "type" : "<ALPHANUM>",
  "position" : 1
}]
```

The only token that is output is कैसी (the second word) because the rest of the words were stop words. (They are common in the Hindi language.)

FILE-BASED STOP WORDS

In the previous examples, we provided a clue to the analyzer about which stop words it should use (English or Hindi) by specifying an off-the-shelf filter. If the built-in stop-word filters don't satisfy our requirements, we can provide stop words via an explicit file.

Let's say we don't want users to input swear words in our application. We can create a file with all the blacklisted swear words and add the path of the file as the parameter to the `standard` analyzer. The file path must be given relative to the config folder of Elasticsearch's installation. The next listing creates an index with an analyzer that accepts a stop-word file.

Listing 7.8 Creating an index with custom stop words in a file

```
PUT index_with_swear_stopwords
{
  "settings": {
    "analysis": {
      "analyzer": {
        "swearwords_analyzer":{
          "type":"standard",
          "stopwords_path":"swearwords.txt"
        }
      }
    }
  }
}
```

Names the analyzer so it can be referenced when indexing/testing

Uses the standard analyzer

The file location must be relative to the config folder.

The `stopwords_path` attribute looks for a file (swearwords.txt, in this case) in a directory inside Elasticsearch's config folder. The following listing creates the file in the config folder. Be sure you change into the $ELASTICSEARCH_HOME/config directory and create a swearwords.txt file there. Notice that each blacklisted word goes on a new line.