Listing 7.9 Blacklisted words in the text file swearwords.txt

```
damn
bugger
bloody hell
what the hell
sucks
```

Once the file is created and the index is developed, we are ready to use the analyzer with our custom-defined swear words.

Listing 7.10 Putting the custom swear words to work

```
POST index_with_swear_stopwords/_analyze
{
  "text": ["Damn, that sucks!"],
  "analyzer": "swearwords_analyzer"
}
```

This code should stop the first and last words from going through the indexing process because they are on our swear words black list. The next attribute we can configure is the length of tokens: how long they should be as output.

CONFIGURING THE TOKEN LENGTH

We can configure the maximum token length to split tokens based on the length we request. For example, listing 7.11 creates an index with a `standard` analyzer. The analyzer is configured to have a maximum token length of seven characters. If we provide a word that is 13 characters long, it will be split into two tokens of seven and six characters (for example, "Elasticsearch" will become "Elastic", "search").

Listing 7.11 Creating an analyzer with a custom token length

```
PUT my_index_with_max_token_length
{
  "settings": {
    "analysis": {
      "analyzer": {
        "standard_max_token_length":{
          "type":"standard",
          "max_token_length":7
        }
      }
    }
  }
}
```

So far, we've worked with the `standard` analyzer. Next on the list of built-in analyzers is the `simple` analyzer, which has the single purpose of splitting text on non-letters. Let's discuss the details of using a `simple` analyzer.