Table 13.2 Sibling pipeline aggregations *(continued)*

Name	Description
Max bucket (`max_bucket`)	Finds the maximum-valued bucket
Min bucket (`min_bucket`)	Finds the minimum-valued bucket
Percentiles bucket (`percentiles_bucket`)	Calculates the percentiles of a metric
Stats bucket (`stats_bucket`)	Calculates common stats for a metric
Sum bucket (`sum_bucket`)	Calculates the sum of a metric

We can't look at all of the pipeline aggregations in this section, but we can review the basics of pipeline aggregations by working through a few common ones. To begin, suppose we want to find cumulative coffee sales: how many cappuccinos are sold daily, for example. Instead of a daily score, we want the total number of cappuccinos sold from the first day of operation, accumulated daily. The `cumulative_sum` aggregation is a handy parent pipeline aggregation that keeps a sum total for the current day, tracks the sum for the next day, and so on. Let's see it in action.

13.5.5 The cumulative_sum parent aggregation

To collect the cumulative sum of coffees sold, we can chain coffee sales by day and pass the results to the `cumulative_sum` pipeline aggregation. The following listing fetches the cumulative sum of cappuccinos sold.

Listing 13.22 Cumulative sales (sum) of cappuccinos sold daily

```
GET coffee_sales/_search
{
  "size": 0,
  "aggs": {
    "sales_by_coffee": {
      "date_histogram": {
        "field": "date",
        "calendar_interval": "1d"
      },
      "aggs": {
        "cappuccino_sales": {
          "sum": {
            "field": "sales.cappuccino"
          }
        },
        "total_cappuccinos": {
          "cumulative_sum": {
            "buckets_path": "cappuccino_sales"
          }
        }
      }
    }
  }
}
```

Parent aggregation that calculates the cumulative total of cappuccino sales