sold. To do this, we need the pipeline aggregation's `max_bucket` and `min_bucket` aggregations, which the next section covers.

13.5.6 The max_bucket and min_bucket sibling pipeline aggregations

Elasticsearch provides a pipeline aggregation called `max_bucket` to fetch the top bucket from the set of buckets fetched from the other aggregations. Remember, a pipeline aggregation takes the input of other aggregations to calculate its own aggregation.

THE MAX_BUCKET AGGREGATION

The query in the following listing enhances the aggregation we performed in the last section. It does this by adding a `max_bucket` function.

Listing 13.23 Pipeline aggregation to find to sales of cappuccinos

```
GET coffee_sales/_search
{
  "size": 0,
  "aggs": {
    "sales_by_coffee": {
      "date_histogram": {
        "field": "date",
        "calendar_interval": "1d"
      },
      "aggs": {
        "cappuccino_sales": {
          "sum": {
            "field": "sales.cappuccino"
          }
        }
      }
    },
    "highest_cappuccino_sales_bucket":{
      "max_bucket": {
        "buckets_path": "sales_by_coffee>cappuccino_sales"
      }
    }
  }
}
```

As you can see in the bold code, `highest_cappuccino_sales_bucket` is the custom name given to the sibling pipeline aggregation we are about to perform. We declare the `max_bucket` aggregation at the same level as the `sales_by_coffee` aggregation, so it is called a sibling aggregation. This expects a `buckets_path`, which combines the aggregations `sales_by_coffee` and `cappuccino_sales`. (These two resulted from bucket and metric aggregations on the data.) When the query is executed, we get this response:

```
"aggregations" : {
  "sales_by_coffee" : {
  "buckets" : [{
    "key_as_string" : "2022-09-01T00:00:00.000Z",
```