```
    "key" : 1661990400000,
    "doc_count" : 1,
    "cappuccino_sales" : {
    "value" : 23.0
  },{
    "key_as_string" : "2022-09-02T00:00:00.000Z",
    "key" : 1662076800000,
    "doc_count" : 1,
    "cappuccino_sales" : {
      "value" : 40.0
      }
    }]
  },
  "highest_cappuccino_sales_bucket" : {
    "value" : 40.0,
    "keys" : [
      "2022-09-02T00:00:00.000Z"
    ]
  }
}
```

The bold portion contains the `highest_cappuccino_sales_bucket` information. The date `2022-09-02` (September 2, 2022) is when the most cappuccinos were sold.

#### THE MIN_BUCKET AGGREGATION

We can also fetch the days when fewer cappuccinos were sold. To do this, we need to use the `min_bucket` pipeline aggregation. Replace the highlighted code in listing 13.23 with the code in the following snippet:

```
..
"lowest_cappuccino_sales_bucket":{
  "min_bucket": {
    "buckets_path": "sales_by_coffee>cappuccino_sales"
  }
}
```

The result shows that the fewest cappuccinos were sold on September 1, 2022:

```
"lowest_cappuccino_sales_bucket" : {
  "value" : 23.0,
  "keys" : [
    "2022-09-01T00:00:00.000Z"
  ]
}
```

There are several other pipeline aggregations like the metric and bucket aggregations. Although it is impractical to discuss all of them in this chapter, the book's code samples include most of the aggregations. Also check the official documentation when you work with a particular aggregation. Here's the link to pipeline aggregations: http://mng.bz/XNzE.

And that's it for aggregations! Let's wrap it up here.