number field with a `pattern` analyzer. Fortunately, Elasticsearch lets us set different analyzers on individual fields as required. Similarly, we can set a default analyzer per index so that any fields not explicitly associated with a specific analyzer during the mapping process inherit the index-level analyzer.

FIELD-LEVEL ANALYZERS

We can specify required analyzers at a field level while creating a mapping definition of an index. The following code shows how we can do this during index creation.

Listing 7.27 Setting field-level analyzers during index creation

```
PUT authors_with_field_level_analyzers
{
  "mappings": {
    "properties": {
      "name":{
        "type": "text"
      },
      "about":{
        "type": "text",
        "analyzer": "english"
      },
      "description":{
        "type": "text",
        "fields": {
          "my":{
            "type": "text",
            "analyzer": "fingerprint"
          }
        }
      }
    }
  }
}
```

Uses the standard analyzer

Explicitly sets the english analyzer

Fingerprint analyzer on a multi-field

The `about` and `description` fields are specified with different analyzers except for the `name` field, which implicitly inherits the `standard` analyzer.

INDEX-LEVEL ANALYZERS

We can also set a default analyzer of our choice at the index level. The following listing demonstrates.

Listing 7.28 Creating an index with a default analyzer

```
PUT authors_with_default_analyzer
{
  "settings": {
    "analysis": {
      "analyzer": {
        "default":{
          "type":"keyword"
```

Setting this property sets the index's default analyzer.