### SETTING THE ANALYZER AT A FIELD LEVEL

The second mechanism sets the search-specific analyzer at the field level. Just as we set an analyzer on a field for indexing purposes, we can add a property called `search_analzyer` on a field to specify the search analyzer.

**Listing 7.31 Setting a search analyzer at the field level**

```
PUT authors_index_with_both_analyzers_field_level
{
  "mappings": {
    "properties": {
      "author_name":{
        "type": "text",
        "analyzer": "stop",
        "search_analyzer": "simple"
      }
    }
  }
}
```

The `author_name` field is set with a `stop` analyzer for indexing and a `simple` analyzer for search time.

### DEFAULT ANALYZER AT THE INDEX LEVEL

We can also set a default analyzer for search queries, just as we did for indexing time, by setting the required analyzer on the index at index-creation time.

**Listing 7.32 Setting default analyzers for search and indexing**

```
PUT authors_index_with_default_analyzer
{
  "settings": {
    "analysis": {
      "analyzer": {
        "default_search":{
          "type":"simple"
        },
        "default":{
          "type":"standard"
        }
      }
    }
  }
}
```

Sets the default search analyzer for the index using the default_search property

Default analyzer for the index

We set the default analyzer for indexing and search at the same time. You may wonder if we can set a search analyzer at the field level during the indexing rather than at run-time during the query. The following listing demonstrates exactly that: it sets different analyzers for indexing and searching at a field level during the creation of an index.