6.9.3 Lifecycle with rollover

In this section, we set conditions on a time-series index to roll over when those conditions are met. Let's say we want the index to be rolled over based on the following conditions:

- On each new day
- When the number of documents hits 10,000
- When the index size reaches 10 GB

The following script defines a simple lifecycle policy declaring a hot phase where the shards are expected to roll over based on these conditions, with a few actions.

Listing 6.50 Simple policy definition for the hot phase

```
PUT _ilm/policy/hot_simple_policy
{
  "policy": {
    "phases": {
      "hot": {
        "min_age": "0ms",
        "actions": {
          "rollover": {
            "max_age": "1d",
            "max_docs": 10000,
            "max_size": "10gb"
          }
        }
      }
    }
  }
}
```

Declares a hot phase

The index enters this phase instantly.

The index rolls over if any of the conditions are met.

In our policy, we declare one phase—the hot phase—with rollover as the action to be performed when any of the conditions declared in the rollover actions are met: for example, if the number of documents reaches 10,000, the index size exceeds 10 GB, or the index is one day old, the index rolls over. Because we declare the minimum age (`min_age`) to be `0ms`, as soon as the index is created, it is instantly moved into the hot phase and then rolled over.

The next step is to create an indexing template and attach the lifecycle policy to it. The following script declares an index template with an index pattern `mysql-*`.

Listing 6.51 Attaching a lifecycle policy to a template

```
PUT _index_template/mysql_logs_template
{
  "index_patterns": ["mysql-*"],
  "template":{
    "settings":{
      "index.lifecycle.name":"hot_simple_policy",
```

Index pattern for all MySQL indexes

Attaches the policy