```
PUT _cluster/settings
{
  "persistent": {
     "indices.lifecycle.poll_interval":"10ms"
  }
}
```

Now that we understand index rollover using lifecycle policies, let's script another policy with multiple phases.

Listing 6.53 Creating an advanced lifecycle policy

```
PUT _ilm/policy/hot_warm_delete_policy
{
  "policy": {
    "phases": {
      "hot": {
        "min_age": "1d",
        "actions": {
          "rollover": {
            "max_size": "40gb",
            "max_age": "6d"
          },
          "set_priority": {
            "priority": 50
          }
        }
      },
      "warm": {
        "min_age": "7d",
        "actions": {
          "shrink": {
            "number_of_shards": 1
          }
        }
      },
      "delete": {
        "min_age": "30d",
        "actions": {
          "delete": {}
        }
      }
    }
  }
}
```

The index waits one day before becoming hot.

Rolls over when one of the conditions is met

Sets the priority (an additional action)

Waits seven days before carrying out the actions

Shrinks the index

Deletes the index, but …

… first stays in this phase for 30 days.

This policy consists of hot, warm, and delete phases. Let's look at what happens and what actions are executed in these phases:

- *Hot phase*—The index enters this phase after one day because the `min_age` attribute is set to `1d`. After one day, the index moves into the rollover stage and waits