Note that we can't use multiples like `5y` (five years) or `4q` (four quarters) when setting the interval using `calendar_interval`. For example, setting the interval as `"calendar_interval": "4q"` results in a parser exception: `"The supplied interval [4q] can not be parsed as a calendar interval"`.

The *fixed interval* (`fixed_interval`) lets us set time intervals as a fixed number of units, such as `365d` (365 days) or `12h` (12 hours). We can use these fixed intervals when we don't need to worry about calendar settings. The accepted values are `days` (`d`), `hours` (`h`), `minutes` (`m`), `seconds` (`s`), and `milliseconds` (`ms`).

Because `fixed_interval` does not know about the calendar, unlike `calendar_interval`, there are no units to support month, year, quarter, and so on. These attributes depend on the calendar (every month has a certain number of days). For example, the following listing fetches all the documents for 730 days (2 years).

Listing 13.12 Histogram with a fixed interval of 2 years (730 days)

```
GET books/_search
{
  "size":0,
  "aggs": {
    "release_date_histogram": {
      "date_histogram": {
        "field": "release_date",
        "fixed_interval": "730d"
      }
    }
  }
}
```

Sets a fixed interval of 2 years (730 days)

The query uses a `fixed_interval` of `730d` (2 years). The results show all books in buckets of exactly 730 days:

```
{
  "key_as_string" : "2017-12-20T00:00:00.000Z",
  "key" : 1513728000000,
  "doc_count" : 11
},
{
  "key_as_string" : "2019-12-20T00:00:00.000Z",
  "key" : 1576800000000,
  "doc_count" : 11
},
{
  "key_as_string" : "2021-12-19T00:00:00.000Z",
  "key" : 1639872000000,
  "doc_count" : 3
}
```

If you are curious, run the same query with two different settings: `"calendar_interval": "1y"` and `"fixed_interval": "365d"`. (The executable code is available with the book's file if you want to experiment with these settings.) After the queries run successfully, check the keys. In the first set of results (with `fixed_interval`: `730d`),