```
            "from": 4,
            "to": 5
          }

        ]
      }
    }
  }
}
```

The query constructs an aggregation with a custom range defined by an array (`ranges`) with only two buckets: from 1 to 4 and from 4 to 5. The following response indicates that two books fall into the 1 to 4 rating and the rest into the 4 to 5 rating:

```
"aggregations" : {
  "book_ratings_range" : {
    "buckets" : [
    {
      "key" : "1.0-4.0",
      "from" : 1.0,
      "to" : 4.0,
      "doc_count" : 2
    },
    {
      "key" : "4.0-5.0",
      "from" : 4.0,
      "to" : 5.0,
      "doc_count" : 35
    }
  ]
 }
}
```

The `range` aggregation is a slight variation of the `histogram` aggregation and well-suited for special or custom ranges that a user may need. Of course, if you want to go with the system-provided categories and don't need customization, a histogram is suitable.

> **NOTE** The `range` aggregation is made up of `from` and `to` attributes. The `from` value is included and the `to` value is excluded when calculating the bucket items that fit this range.

By the same principle, we can classify IP addresses in a custom range using a dedicated `ip_range` aggregation. The next listing shows that. (Note that this code is for demonstrative purposes only—we do not have a `networks` index primed with data consisting of the `localhost_ip_address` field.)

Listing 13.15 Classifying IP addresses in to two baskets

```
GET networks/_search
{
  "aggs": {
```