```
    "my_ip_addresses_custom_range": {
      "ip_range": {
        "field": "localhost_ip_address",
        "ranges": [
          {
            "to": "192.168.0.10",
            "from": "192.168.0.20"
          },
{
            "to": "192.168.0.20",
            "from": "192.168.0.100"

          }
        ]
      }
    }
  }
}
```

The ip_range bucketing segregates certain IPs into given buckets.

Defines the custom range of IP addresses that are expected to be categorized

Runs the range aggregation on this field (must be of type ip)

As you can see from this sample aggregation, we can segregate IP addresses based on our custom ranges. The query produces two ranges: one that includes `192.168.0.10` to `192.168.0.20` and the second with `192.168.0.20` to `192.168.0.100`.

13.3.4 The terms aggregation

When we want to retrieve an aggregated count of a certain field, such as authors and their book count, the `terms` aggregations comes in handy. The `terms` aggregation collects data in buckets for each occurrence of the term. For example, in the following query, the `terms` aggregation creates a bucket for each author and the number of books they've written.

Listing 13.16 Aggregated count of books by author

```
GET books/_search?size=0
{
  "aggs": {
    "author_book_count": {
      "terms": {
        "field": "author.keyword"
      }
    }
  }
}
```

Declares the terms aggregation type

Applies the aggregation to this field

The query uses the `terms` aggregation to fetch the list of authors in the `books` index and their book count. The response indicates that `key` is the author, and `doc_count` shows the number of books for each author:

```
"buckets" : [
  {
    "key" : "Herbert Schildt",
    "doc_count" : 2
  },
```